

Kodak Water-Resistant Scrim Banner / 16 mil

KODAK Water-Resistant Scrim Banner raises the performance bar by providing a scratch- and water-resistant surface with a white point never before seen on a banner substrate. KODAK Water-Resistant Scrim Banner is a 16-mil, scrim-reinforced vinyl designed to create spectacular, high-impact, cost-effective graphics that will stand up to the test of time. KODAK Water-Resistant Scrim Banner not only extends the life of the graphic, it also provides easier handling, creating efficiency in production so that users can compete for high-volume banner jobs with the one-two punch of economy and quality. It is compatible with both thermal and piezo printing technologies.

Properties	Specifications
Material	Tear-resistant polyester fabric embedded between two white vinyl layers
Gauge	16 mil
Weight	450 g/m ²
Opacity	>95
Color	L* = 89 - 92, a* = 4.0 ± 2.0, b* = -12.0 ± 3.0
Whiteness	≥ 130 (CIE)
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigmented-based inks.
Software Setting	When using this material with Encad GO inks, utilize the UCR (Under Color Removal) technique that replaces composite black (CMY) with the appropriate amount of black ink. To optimize print quality, printers should be set for the highest print quality and media selection should be set on "heavy coated." Ink coverage up to 250% is recommended.
Color Matching	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software.
Lightfastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. All dye-based inks fade noticeably under direct sunlight, in interior applications where direct sunlight may fall on an image, and/or where fluorescent or other UV lighting is present. Although the fading process is inherent with all inkjet inks, certain UV enhanced inks, pigment-based inks, and UV inhibiting laminates will extend the longevity of an image. Contact the ink manufacturer to determine suitability for a particular application.
Finishing/Post Processing	Pressure sensitive vinyl laminates with UV inhibitors can be applied to increase the fade and abrasion resistance of the image. Polyester or other base material laminates are not recommended. Before applying the laminate, allow the image to dry for 24 hours.

Product Performance & Suitability: All of the descriptive information and recommendations for the use of Kodak products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by BMG. All Purchasers of Kodak products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor the manufacturer shall be liable either in the tort in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect in agreement signed by officers of seller and manufacturer.



KODAK Water-Resistant Scrim Banner

For more information, contact BMG at: 1-888-893-4668



©Brand Management Group, 2013
The Kodak and Kodak Professional trademarks and Kodak trade dress are used under license from Kodak.