**GreenStar DRY ERASE VINYL** 

Description

Calendered vinyl custom formulated for interior use with dry erase type markers. Available in clear and

white. Clear can be used as a laminate over digital prints. Material may be written on repeatedly; wipes

clean with dry tissue or dry erase cleaning fluid. (DO NOT USE ANY OTHER CLEANERS.) Do not use

with Premask Plus or any other application tape. Not recommended for thermal printing.

**Physical Properties** 

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the

suitability of this material for his/her specific purpose. (Data represents averages and is not intended for

use as a specification).

Outdoor Durability: None. For interior use only.

**Application Temperature**: +40° F (Note: Do not use wet application method)

**Service Temperature Range**: -40° F to 180° F

Thickness: 4.0 mil

Typical Adhesion Values: 180° Peel Test Substrate 24 hrs

Stainless steel 4.4 lbs/in

Note: Tested per ASTM 1000.

Always pretest your specific substrate prior to actual application.

**Dimensional Stability**: No measurable shrinkage

Shelf Life: 1 year at temperatures under 70° F (21° C) 50 ± 5% R.H.

Chemical Resistance: Resistant to mild acids, alkalies, salts, and most petroleum based oil, grease and

aliphatic solvents.