## GreenStar "EDGE" Adhesive Backed - Wall Graphic Fabric FOR LATEX & SOLVENT PRINTERS

Sticks to any non-porous flat surface. Removable, reusable, repositionable and removes with no residue

For indoor and outdoor applications, including windows, doors, sign boards and other flat surfaces

Print to edge - no border needed around printed graphics. Compatible with OEM Latex, Solvent and Mild Solvent Inks

Construction: Product Number: GS-SOL/WALLFABRIC/36or54

Adhesive: Removable Repositionable Acrylic

Film: 100% Polyester Woven Polyester Caliper/Gauge: 360 grans - 14 mil with liner - 7 mil with adhesive no liner

Liner: 90 lb Polycoated two sides

Finish: Matte White

Gloss Level: >10 (avg.) @ 60°

Typical Performance Values:

The following information on physical and chemical characteristics is based upon tests believed

to be reliable. The values are intended only as a source of information. They are given without

guarantee and do not constitute a warranty. The purchaser should independently determine,

prior to use, the suitability of this material for his/her specific purpose. (Data represents

averages and is not intended for use as a specification.)

Durability: Varies by application, interior 36 months or greater, typical.

*Minimum Application Temperature*: + 50° F (Minimum for Substrate)

Service Temperature Range: -40° F to + 180° F

Typical Adhesion Values: 180° Peel Test Substrate 24 hrs. Stainless Steel 2.0 lb/in

Shelf Life: 1 year from ship date when stored in proper conditions 70° F and 50% relative humidity