GreenStar Adhesive Backed 2 mil Gloss White Cast Vinyl Permanent Gray Adhesive & Air Release Liner

for Solvent, Latex & UV Printers

- Premium high performance, flexible cast vinyl for application to irregular surfaces.
- Perfect for recreational vehicle, fleet, marine, automotive and architectural signage.
- The textured liner has embossed pattern that produces channels in the adhesive that will help air to escape during application.
- Repositionable adhesive is gray for increased opacity and blockout.
- Compatible with OEM Solvent, Latex & UV Curable Inks Construction

Product Number: GS-SOL/WHITECAST/xxAR

Adhesive: Repositionable Permanent Gray Acrylic Film:

2 mil Cast Vinyl Liner: Air Release 90# Lay Flat Finish:

Gloss Clear Gloss Level: 80 (avg.) @ 60°

Typical Performance Values: The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Printing: 7 years - Vertical exposure - Unprinted Minimum Application Temperature: +55° F (Minimum for Substrate)

Service Temperature Range: 50° F to +225° F Dimensional Stability: 0.01 in. (48 hrs. @ 150° F) (applied to an aluminum panel)

Chemical Resistance: Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvents and salts.

Typical Adhesion Values: 180° Peel Test Substrate 24 hrs. Stainless Steel 2 lb/in

Shelf Life: 1 year from ship date when stored in proper conditions 70° F and 50% relative humidity

Standard Warranty All statements, technical information and recommendations about GreenStar products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All GreenStar products are sold with the understanding that the Purchaser has independently determined

the suitability of such product for its purposes. GreenStar products are warranted to be free from defects in material and workmanship for either one year (or the period stated on the specific product information literature in effect at time of delivery, if longer) from date of shipment if said product is properly stored and applied. It is expressly agreed and understood that GreenStar's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited to repair or replacement of defective product without charge at GreenStar's plant or at the location of product (at GreenStar's election), or in the event replacement or repairs is not commercially practical, to GreenStar's issuing Purchaser a credit reasonable in light of the defect in the product.

GreenStar's liability for defective products shall not exceed the purchase price paid therefore by Purchaser and in no event shall GreenStar be responsible for any incidental or consequential damages whether foreseeable or not, caused by defects in such product, whether such damage occurs or is discovered before or after replacement or credit, and whether or not such damage is caused by GreenStar's negligence.

No express warranties and no implied warranties, whether of merchantability or fitness for any particular use, or otherwise (except as to title) other than those expressly set forth above which are made expressly in lieu of all other warranties, shall apply to products sold by GreenStar. GreenStar specifically disclaims and excludes all other such warranties, no waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and manually signed by an officer of GreenStarMedia.com