



HIGHBAKE PAINT MASK

Film: 80um yellow calendared vinyl Adhesive: clear removable acrylic, Liner: 150gsm clay-coated paper

Specifications:

- Construction: Calendared PVC Film
- Acrylic Adhesive
- Clay-coated Paper Liner
- Weight: 3.8 oz/sq. yd. – film + adhesive
- 4.5-5 oz/sq. yd. - liner
- Film Thickness: 3 mil
- Standard Width: 15", 24"
- Standard Colors: Yellow – film
- Clear - adhesive
- Adhesive Strength: 2.7 lb/1" (PSTC 101 Test Method A, after 24 hours)
- Temperature Range: -40°F to 203°F
- Removes clean after exposure to up to 200°F.

Key Features & Benefits:

- Film
 - Thickness: 81µm (3.2 mil)
 - Film type: calendared vinyl
 - Color: Yellow Elongation at break: MIN 100%
- Adhesive
 - Thickness: 25 µm (1 mil)
 - Base: Clear REMOVABLE Acrylic
 - Adhesive Strength: after 24 hour 385N/m (2.17 lbs/1")
 - Temperature range: -40°C to +95°C (-40°F to 203°F). Must be able to remove clean after exposure to up to 200°F.
 - Must be removable from most OEM paints
- Liner:
 - Type: 78# kraft paper
 - Dimensionally stable

Application Settings:

- Heat and Dwell: 200°F oven 20 minutes bake / 20 minutes cool/repeat)

USCutter

Questions? Contact USCutter Sales at 425-481-3555 or visit USCutter.com